

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS219084T |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 4730-01-289-0753 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |

NO IMAGE
AVAILABLE

P/N MS21908-4T Specifications

| | |
|---|---|
| Thread Class: | 3a 1st End Bulkhead |
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit Single Response |
| Connection Style: | Flareless (tube) All Ends |
| Leg Length: | 1.500 Inches Nominal 1st End |
| Leg Length: | 0.938 Inches Nominal 2nd End |
| Connection Type: | Threaded External Tube All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.438 Inches 1st End Bulkhead |
| Nominal Thread Size: | 0.438 Inches All Ends |
| Seat Angle: | 12.0 Degrees All Ends |
| Flow Angle: | 90.0 Degrees |
| Nominal Outside Diameter Tube Accommodated: | 0.250 Inches All Ends |
| Material: | Titanium Alloy Overall |
| Media For Which Designed: | Hydraulic Fluid Single Response |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf All Ends |
| Thread Series Designator: | Unjf 1st End Bulkhead |
| Specification/standard Data: | 96906-ms21908-4t Government Standard |

How to Order

Order this elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21908-4T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.