

Description

outside 3/8", bulkhead universal, flareless tube, 90 degree, carbon steel, MS21908 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21908V6P](#)

SKU / Model:	MS219086
Minimum Qty (MOQ):	1
NSN:	4730-01-542-6351
Schedule B:	7307.92.9000
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



* See page 2 for technical characteristics

P/N MS21908-6 Specifications

Thread Class:	3a All Ends
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.063 Inches Minimum 2nd End And 1.100 Inches Maximum 2nd End
Leg Length:	1.688 Inches Minimum 1st End And 1.735 Inches Maximum 1st End
Connection Type:	Threaded External Tube All Ends
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.375 Inches All Ends
Part Name Assigned By Controlling Agency:	Elbow, Bulkhead Universal 90, Flareless Tube
Special Features:	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated; First End Has Bulkhead Threads
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	81343 - As21908 Professional/industrial Association Standard

How to Order

Order this tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21908-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.