

**Description**

Thread Size: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS219086T
Minimum Qty (MOQ):	1 EA
NSN:	4730-01-291-4069
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N MS21908-6T Specifications

<b>Thread Class:</b>	3a 1st End Bulkhead
<b>Thread Class:</b>	3a All Ends
<b>Maximum Operating Temp:</b>	275.0 Deg Fahrenheit Single Response
<b>Connection Style:</b>	Flareless (tube) All Ends
<b>Leg Length:</b>	1.062 Inches Nominal 2nd End
<b>Leg Length:</b>	1.688 Inches Nominal 1st End
<b>Connection Type:</b>	Threaded External Tube All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.562 Inches 1st End Bulkhead
<b>Nominal Thread Size:</b>	0.562 Inches All Ends
<b>Seat Angle:</b>	12.0 Degrees All Ends
<b>Flow Angle:</b>	90.0 Degrees
<b>Nominal Outside Diameter Tube Accommodated:</b>	0.375 Inches All Ends
<b>Material:</b>	Titanium Alloy Overall
<b>Media For Which Designed:</b>	Hydraulic Fluid Single Response
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-4156 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Thread Series Designator:</b>	Unjf 1st End Bulkhead
<b>Specification/standard Data:</b>	96906-ms21908-6t Government Standard

## How to Order

Order this elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21908-6T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.