

## Description

Thread Size: 1"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21908J12                                  |
| Minimum Qty (MOQ):      | 1 EA  |
| NSN:                    | 4730-00-816-6801                            |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21908J12 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a 1st End Bulkhead  |
| <b>Thread Class:</b>                                  | 3a All Ends  |
| <b>Maximum Operating Temp:</b>                        | 275.0 Deg Fahrenheit Single Response   |
| <b>Connection Style:</b>                              | Flareless (tube) All Ends  |
| <b>Leg Length:</b>                                    | 1.625 Inches Nominal 2nd End   |
| <b>Leg Length:</b>                                    | 2.469 Inches Nominal 1st End   |
| <b>Connection Type:</b>                               | Threaded External Tube 1st End Bulkhead  |
| <b>Connection Type:</b>                               | Threaded External Tube All Ends  |
| <b>Thread Quantity Per Inch:</b>                      | 12 1st End Bulkhead  |
| <b>Thread Quantity Per Inch:</b>                      | 12 All Ends  |
| <b>Maximum Operating Pressure:</b>                    | 3000.0 Pounds Per Square Inch Single Response                                    |
| <b>Nominal Thread Size:</b>                           | 1.062 Inches 1st End Bulkhead  |
| <b>Nominal Thread Size:</b>                           | 1.062 Inches All Ends  |
| <b>Seat Angle:</b>                                    | 12.0 Degrees All Ends  |
| <b>Flow Angle:</b>                                    | 90.0 Degrees   |
| <b>Nominal Outside Diameter Tube Accommodated:</b>    | 0.750 Inches All Ends  |
| <b>Material:</b>                                      | Steel Comp 304 Overall   |
| <b>Material Document And Classification:</b>          | Qq-s-763 Fed Spec Single Material Response Overall                               |
| <b>Media For Which Designed:</b>                      | Aeronautical Fluid Single Response   |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-s-5002 Mil Spec Single Treatment Response Overall                            |
| <b>Thread Series Designator:</b>                      | Unj 1st End Bulkhead   |
| <b>Thread Series Designator:</b>                      | Unj All Ends   |
| <b>Specification/standard Data:</b>                   | 96906-ms21908 Government Standard And 81349-mil-f-18280 Government Specification |

## How to Order

Order this elbow from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21908J12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.