

# P/N MS21908J12

### **Description**

Thread Size: 1"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS21908J12

Minimum Qty (MOQ): 1 EA

NSN: 4730-00-816-6801

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



<sup>\*</sup> See page 2 for technical characteristics

## P/N MS21908J12 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.625 Inches Nominal 2nd End
Leg Length:	2.469 Inches Nominal 1st End
Connection Type:	Threaded External Tube 1st End Bulkhead
Connection Type:	Threaded External Tube All Ends
Thread Quantity Per Inch:	12 1st End Bulkhead
Thread Quantity Per Inch:	12 All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	1.062 Inches 1st End Bulkhead
Nominal Thread Size:	1.062 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.750 Inches All Ends
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Media For Which Designed:	Aeronautical Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unj 1st End Bulkhead
Thread Series Designator:	Unj All Ends
Specification/standard Data:	96906-ms21908 Government Standard And 81349-mil-f-18280 Government Specification

## **How to Order**

Order this elbow from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/MS21908J12">https://military-fasteners.com/bolts/shear+bolts/MS21908J12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.