

Description

Thread Size: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21908J8
Minimum Qty (MOQ):	1 EA
NSN:	4730-00-720-0983
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21908J8 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.312 Inches Nominal 2nd End
Leg Length:	1.969 Inches Nominal 1st End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.750 Inches 1st End Bulkhead
Nominal Thread Size:	0.750 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.500 Inches All Ends
Material:	Steel Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	96906-ms21908 Government Standard

How to Order

Order this elbow from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21908J8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.