

**Description**

outside diameter: 1/4", MS21908 series fitting (New Revision)

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21908V4P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-6345
ECCN:	9A991.d
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



\* See page 2 for technical characteristics

## P/N MS21908V4P Specifications

<b>Thread Class:</b>	3a All Ends
<b>Connection Style:</b>	Flareless (tube) All Ends
<b>Leg Length:</b>	1.500 Inches Minimum 1st End And 1.547 Inches Maximum 1st End
<b>Leg Length:</b>	0.938 Inches Minimum 2nd End And 0.985 Inches Maximum 2nd End
<b>Connection Type:</b>	Threaded External Tube All Ends
<b>Nominal Thread Size:</b>	0.438 Inches All Ends
<b>Seat Angle:</b>	12.0 Degrees All Ends
<b>Flow Angle:</b>	90.0 Degrees
<b>Nominal Outside Diameter Tube Accommodated:</b>	0.250 Inches All Ends
<b>Part Name Assigned By Controlling Agency:</b>	Elbow, Bulkhead Universal 90, Flareless Tube
<b>Special Features:</b>	Material Corrosion Resistant Steel (15-5ph) Cadmium Plated; First End Has Bulkhead Threads
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	81343 - As21908 Professional/industrial Association Standard

## How to Order

Order this tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21908V4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.