

## P/N MS21908W10

## **Description**

Thread Size: 7/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21908W10
Minimum Qty (MOQ): 1 EA
NSN: 4730-00-483-4938
National Motor Freight: 051400, Pipe Fittings Aluminum



# P/N MS21908W10 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	-54.0 Deg Celsius 1st Response
Maximum Operating Temp:	135.0 Deg Celsius 2nd Response
End Item Identification:	16n Aircraft, Viking S-3a
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.500 Inches Nominal 2nd End
Leg Length:	2.250 Inches Nominal 1st End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.875 Inches 1st End Bulkhead
Nominal Thread Size:	0.875 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.625 Inches All Ends
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-367,t73 Fed Spec Single Material Response Overall
Media For Which Designed:	Aeronautical Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625,ty2,cl 2 Mil Spec Single Treatment Response Outside
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead

### **How to Order**

Order this elbow from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/MS21908W10">https://military-fasteners.com/bolts/shear+bolts/MS21908W10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.