

Description

Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21908W3
Minimum Qty (MOQ):	1 EA
NSN:	4730-00-451-1035
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21908W3 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	-54.0 Deg Celsius 1st Response
Maximum Operating Temp:	135.0 Deg Celsius 2nd Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.391 Inches Nominal 1st End
Leg Length:	0.906 Inches Nominal 2nd End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.375 Inches 1st End Bulkhead
Nominal Thread Size:	0.375 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.188 Inches All Ends
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-367,t73 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Outside
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead

How to Order

Order this elbow from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21908W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.