

Description

tube outside diameter: 1/4", aluminum alloy, bulkhead universal, flareless tube, 90Deg

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21908D4](#)

SKU / Model:

MS21908W4

Minimum Qty (MOQ):

1

NSN:

4730-00-173-5160

ECCN:

EAR99

National Motor Freight:

051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21908W4 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Leg Length:	1.500 Inches Nominal 1st End
Leg Length:	0.938 Inches Nominal 2nd End
Connection Type:	Threaded External Tube 1st End Bulkhead
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches 1st End Bulkhead
Nominal Thread Size:	0.438 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.250 Inches All Ends
Reduced Passage Nominal Inside Diameter:	0.188 Inches All Ends
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-367,t73 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	96906-ms21908 Government Standard

How to Order

Order this tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/MS21908W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.