

# P/N MS21912D16

Military-Fasteners.com

#### Description

Anodize overall, flareless, MS21912 series fitting

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

#### Order this part online

#### **Additional Information**

SKU / Model:	MS21912D16
Minimum Qty (MOQ):	1
NSN:	4730-00-640-5120
National Motor Freight:	051400, Pipe Fittings Aluminum



## P/N MS21912D16 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	250.0 Deg Fahrenheit Single Response
End Item Identification:	Used On Boeing Vertol Cargo Transport Helicopter, Model Ch-47
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.719 Inches Nominal 2nd End
Leg Length:	1.719 Inches Nominal 3rd End
Leg Length:	2.594 Inches Nominal 1st End
Connection Type:	Threaded External Tube All Ends
Thread Quantity Per Inch:	12 1st End Bulkhead
Thread Quantity Per Inch:	12 All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	1.312 Inches All Ends
Nominal Thread Size:	1.312 Inches 1st End Bulkhead
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	1.000 Inches All Ends
Material:	Aluminum Alloy 2014 Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unj 1st End Bulkhead
Thread Series Designator:	Unj All Ends
Specification/standard Data:	96906-ms21912 Government Standard

### How to Order

Order this tube tee from our inventory online by visiting <u>https://military-fasteners.com/fittings/tube+tees/MS21912D16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.