

Description

Thread Size: 0-3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21912D5
Minimum Qty (MOQ):	1
NSN:	4730-00-289-4208
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21912D5 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	225.0 Deg Fahrenheit 1st Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.031 Inches Nominal 3rd End
Leg Length:	1.031 Inches Nominal 2nd End
Leg Length:	1.531 Inches Nominal 1st End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.500 Inches 1st End Bulkhead
Nominal Thread Size:	0.500 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.312 Inches All Ends
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-367,t6 Fed Spec 1st Material Response Overall Or Qq-a-367,t73 Fed Spec 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2,light Tan Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	96906-ms21912 Government Standard

How to Order

Order this tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/MS21912D5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.