

Description

Thread Size: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS21912D8 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-246-9519 |
| ECCN: | 9A991 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |

NO IMAGE
AVAILABLE

P/N MS21912D8 Specifications

| | |
|---|---|
| Thread Class: | 3a 1st End Bulkhead |
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit Single Response |
| Connection Style: | Flareless (tube) All Ends |
| Leg Length: | 1.313 Inches Nominal 2nd End |
| Leg Length: | 1.313 Inches Nominal 3rd End |
| Leg Length: | 1.969 Inches Nominal 1st End |
| Connection Type: | Threaded External Tube All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.750 Inches 1st End Bulkhead |
| Nominal Thread Size: | 0.750 Inches All Ends |
| Seat Angle: | 12.0 Degrees All Ends |
| Nominal Outside Diameter Tube Accommodated: | 0.500 Inches All Ends |
| Special Features: | Material Aluminum Alloy 7075 |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | Qq-a-367,t6 Fed Spec Single Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid Single Response |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf All Ends |
| Thread Series Designator: | Unjf 1st End Bulkhead |
| Specification/standard Data: | 96906-ms21912 Government Standard |

How to Order

Order this tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/MS21912D8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.