

Description

Thread Size: 35/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21912J6
Minimum Qty (MOQ):	1
NSN:	4730-00-201-8506
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21912J6 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	137.0 Deg Fahrenheit 2nd Response
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.063 Inches Nominal 2nd End
Leg Length:	1.063 Inches Nominal 3rd End
Leg Length:	1.688 Inches Nominal 1st End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch 1st Response
Nominal Thread Size:	0.562 Inches 1st End Bulkhead
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.375 Inches All Ends
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Media For Which Designed:	Water-oil-gas 2nd Response
Media For Which Designed:	Aeronautical Fluid 1st Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	96906-ms21912 Government Standard

How to Order

Order this tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/MS21912J6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.