

P/N MS21912W10

Description

Thread Size: 7/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS21912W10
Minimum Qty (MOQ):	1
NSN:	4730-00-640-5118
ECCN:	9A991
National Motor Freight:	051400, Pipe Fittings Aluminum



^{*} See page 2 for technical characteristics

P/N MS21912W10 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
End Item Identification:	Aircraft Application
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.500 Inches Nominal 2nd End
Leg Length:	1.500 Inches Nominal 3rd End
Leg Length:	2.250 Inches Nominal 1st End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.875 Inches 1st End Bulkhead
Nominal Thread Size:	0.875 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.625 Inches All Ends
Material:	Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-367,temper T6 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	96906-ms21912 Government Standard

How to Order

Order this tube tee from our inventory online by visiting https://military-fasteners.com/fittings/tube+tees/MS21912W10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.