

## P/N MS21913-5

## **Description**

outside diameter: 5/16", hex head, flareless tube, carbon steel, MS21913 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### MS21913V5P

SKU / Model: MS219135

Minimum Qty (MOQ): 2

NSN: 4730-00-541-1465

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti









# P/N MS21913-5 Specifications

Thread Class:	3a External
Thread Pitch Diameters:	+0.4919/+0.5000 Inches External
Thread Direction:	Right-hand External
Head Height:	0.172 Inches Minimum And 0.218 Inches Maximum
Overall Length:	0.671 Inches Nominal
End Item Identification:	Brf Engine, Aircraft, Tf39-ge-1 (c-5a)
Connection Style:	Flareless
Nominal Thread Size:	0.500 Inches External
Material:	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

## **How to Order**

Order this threaded tube fitting plug from our inventory online by visiting <a href="https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913-5">https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.