

Description

outside diameter: 5/16", hex head, flareless tube, carbon steel, MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS21913V5P

SKU / Model:	MS219135
Minimum Qty (MOQ):	2
NSN:	4730-00-541-1465
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21913-5 Specifications

Thread Class:	3a External
Thread Pitch Diameters:	+0.4919/+0.5000 Inches External
Thread Direction:	Right-hand External
Head Height:	0.172 Inches Minimum And 0.218 Inches Maximum
Overall Length:	0.671 Inches Nominal
End Item Identification:	Brf Engine, Aircraft, Tf39-ge-1 (c-5a)
Connection Style:	Flareless
Nominal Thread Size:	0.500 Inches External
Material:	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.