

**Description**

outside diameter: 5/8", hex head, flareless tube, aluminum alloy, MS21913 series plug

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS21913W10](#)

SKU / Model:	MS21913D10
Minimum Qty (MOQ):	1
NSN:	4730-00-203-0247
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

# P/N MS21913D10 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.359 Inches Nominal
<b>Overall Length:</b>	0.984 Inches Nominal
<b>End Item Identification:</b>	Helicopter,utility-tactical Transport,uH-1 And Eh-1 (bell)
<b>Connection Style:</b>	Flareless
<b>Nominal Thread Size:</b>	0.875 Inches External
<b>Seat Angle:</b>	12.0 Degrees
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-225/6,t6,t62 Or T851 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
<b>Style Designator:</b>	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
<b>Thread Series Designator:</b>	Unjf External
<b>Specification/standard Data:</b>	96906-ms21913 Government Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913D10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.