

## Description

tube outside diameter: 3/8", hex head, flareless tube, aluminum alloy 2024, MS21913 series plug

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[MS21913W6](#)

SKU / Model:	MS21913D6
Minimum Qty (MOQ):	5
NSN:	4730-00-555-7804
Schedule B:	7619.00.0000
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

# P/N MS21913D6 Specifications

Thread Direction:	Right-hand External
Head Height:	0.260 Inches Minimum And 0.334 Inches Maximum
Overall Length:	0.718 Inches Minimum And 0.728 Inches Maximum
End Item Identification:	Fan Virginia Class Cgn (41)
Connection Style:	Flareless
Nominal Thread Size:	0.562 Inches External
Seat Angle:	12.0 Degrees
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential;aajd Was 3a
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-b-225/6,t6 Fed Spec 1st Material Response Overall Or Qq-b-225/6,t6 Fed Spec 2nd Material Response Overall
Surface Treatment:	Anodize Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913D6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.