

Description

aluminum alloy, tube outside 1/2", plug hex head, flareless tube. Superseded by MS21913W8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21913-D8](#) [MS21913W8](#)

| | |
|-------------------------|------------------------------------|
| SKU / Model: | MS21913D8 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-202-8860 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N MS21913D8 Specifications

| | |
|---------------------------------------|---|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Head Height: | 0.281 Inches Nominal |
| Overall Length: | 0.844 Inches Nominal |
| End Item Identification: | Helicopter,utility-tactical Transport,uH-1 And EH-1 (bell) |
| iii End Item Identification: | Helicopter,utility-tactical Transport,uH-1 And EH-1 (bell); Mrap Buffalo Mk2a2 |
| Connection Style: | Flareless |
| Nominal Thread Size: | 0.750 Inches External |
| Seat Angle: | 12.0 Degrees |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | QQ-A-225/6,t6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic) |
| Thread Series Designator: | UNJF External |
| Specification/standard Data: | 96906-MS21913 Government Standard |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913D8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.