

P/N MS21913J10

Description

tube outside diameter: 5/8", plug hex head, flareless tube, corrosion resistant steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS21913J10

Minimum Qty (MOQ):


NSN: 4730-00-081-3459

ECCN: 9A991

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti









^{*} See page 2 for technical characteristics

P/N MS21913J10 Specifications

| Thread Class: | 3a External |
|---------------------------------------|--|
| Thread Direction: | Right-hand External |
| Head Height: | 0.359 Inches Nominal |
| Overall Length: | 0.984 Inches Nominal |
| End Item Identification: | Aircraft Fluid System |
| Connection Style: | Inverted Flare |
| Nominal Thread Size: | 0.875 Inches External |
| Seat Angle: | 12.0 Degrees |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic) |
| Thread Series Designator: | Unjf External |
| Specification/standard Data: | 96906-ms21913 Government Standard |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913J10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.