

Description

tube outside diameter: 1/4", corrosion resistant steel (304), hex head, flareless tube, MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21913J4 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-053-1919 |
| Schedule B: | 7307.22.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



P/N MS21913J4 Specifications

| | |
|--|---|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Head Height: | 0.203 Inches Nominal |
| Overall Length: | 0.641 Inches Nominal |
| Connection Style: | Flareless |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch |
| Nominal Thread Size: | 0.438 Inches External |
| Seat Angle: | 12.0 Degrees |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Media For Which Designed: | Fuel/oil, Hydrocarbon |
| Surface Treatment: | Passivate Overall |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic) |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic) |
| Thread Series Designator: | Unjf External |
| Specification/standard Data: | 96906-ms21913 Government Standard |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913J4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.