

P/N MS21913J4

Description

tube outside diameter: 1/4", corrosion resistant steel (304), hex head, flareless tube, MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21913J4

Minimum Qty (MOQ):

NSN: 4730-00-053-1919

Schedule B: 7307.22.5000

ECCN: EAR99

National Motor Freight: 052190, Pipe, tubing, or Pipe Or Tubing Fitti









^{*} See page 2 for technical characteristics

P/N MS21913J4 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.203 Inches Nominal
Overall Length:	0.641 Inches Nominal
Connection Style:	Flareless
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.438 Inches External
Seat Angle:	12.0 Degrees
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Fuel/oil, Hydrocarbon
Surface Treatment:	Passivate Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913J4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.