

**Description**

Tube outside diameter: 1/2", corrosion resistant steel, hex head, flareless tube, MS21913 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21913J8
Minimum Qty (MOQ):	1
NSN:	4730-00-813-7441
Schedule B:	7307.22.5000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



\* See page 2 for technical characteristics

## P/N MS21913J8 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.282 Inches Nominal
<b>Overall Length:</b>	0.844 Inches Nominal
<b>Connection Style:</b>	Flareless
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.750 Inches External
<b>Seat Angle:</b>	12.0 Degrees
<b>Material:</b>	Steel Comp 304 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Media For Which Designed:</b>	Water, Fresh
<b>Surface Treatment:</b>	Passivate Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
<b>Thread Series Designator:</b>	Unjf External
<b>Specification/standard Data:</b>	96906-ms21913 Government Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913J8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.