

Description

Tube outside diameter: 1/2", corrosion resistant steel, hex head, flareless tube, MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21913J8
Minimum Qty (MOQ):	1
NSN:	4730-00-813-7441
Schedule B:	7307.22.5000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N MS21913J8 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.282 Inches Nominal
Overall Length:	0.844 Inches Nominal
Connection Style:	Flareless
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.750 Inches External
Seat Angle:	12.0 Degrees
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Water, Fresh
Surface Treatment:	Passivate Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913J8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.