

Description

corrosion resistant steel (15-5ph), cadmium plated, tube outside 3/4", plug hex head, flareless tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21913V12P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-7314
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS21913V12P Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.343 Inches Nominal
Overall Length:	1.031 Inches Nominal
Maximum Operating Temp:	275.0 Deg Fahrenheit
iii End Item Identification:	Mrap Buffalo Mk2a2
Connection Style:	Flareless
Thread Quantity Per Inch:	12 External
Maximum Operating Pressure:	1500.0 Pounds Per Square Inch
Nominal Thread Size:	1.062 Inches External
Seat Angle:	12.0 Degrees
Part Name Assigned By Controlling Agency:	Plug, Flareless Tube
Special Features:	Corrosion Resistant Steel (15-5ph) With Cadmium Plating
Material:	Steel Comp 15-5ph Overall
Media For Which Designed:	Hydraulic Fluid
Surface Treatment:	Cadmium Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Thread Series Designator:	Unj External
Specification/standard Data:	81343-as21913 Professional/industrial Association Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913V12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.