

Description

outside diameter: 1/8", hex head, flareless tube, corrosion resistant steel, cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**MS21913-2

| | |
|-------------------------|---|
| SKU / Model: | MS21913V2P |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-01-542-7608 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N MS21913V2P Specifications

| | |
|--|--|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Head Height: | 0.188 Inches Nominal |
| Overall Length: | 0.563 Inches Nominal |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit |
| Connection Style: | Flareless |
| Maximum Operating Pressure: | 1500.0 Pounds Per Square Inch |
| Nominal Thread Size: | 0.313 Inches External |
| Seat Angle: | 12.0 Degrees |
| Part Name Assigned By Controlling Agency: | Plug, Flareless Tube |
| Special Features: | Corrosion Resistant Steel (15-5ph) With Cadmium Plating |
| Material: | Steel Comp 15-5ph Overall |
| Media For Which Designed: | Hydraulic Fluid |
| Surface Treatment: | Cadmium Overall |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic |
| Thread Series Designator: | Unjf External |
| Specification/standard Data: | 81343-as21913 Professional/industrial Association Standard |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913V2P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.