

# P/N MS21913V4P

Military-Fasteners.com

#### Description

outside diameter: 1/4", corrosion resistant steel, cadmium plated, plug hexagon head, flareless, MS21913 series fitting


\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

MS21913-4	
SKU / Model:	MS21913V4P
Minimum Qty (MOQ):	2
NSN:	4730-01-542-7624
Schedule B:	7307.22.5000
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



### P/N MS21913V4P Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.203 Inches Nominal
Overall Length:	0.641 Inches Nominal
Maximum Operating Temp:	275.0 Deg Fahrenheit
Connection Style:	Flareless
Maximum Operating Pressure:	1500.0 Pounds Per Square Inch
Nominal Thread Size:	0.438 Inches External
Seat Angle:	12.0 Degrees
Part Name Assigned By Controlling Agency:	Plug, Flareless Tube
Special Features:	Corrosion Resistant Steel (15-5ph) With Cadmium Plating
Material:	Steel Comp 15-5ph Overall
Media For Which Designed:	Hydraulic Fluid
Surface Treatment:	Cadmium Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Thread Series Designator:	Unjf External
Specification/standard Data:	81343-as21913 Professional/industrial Association Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <u>https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913V4P</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.