

Description

carbon steel, tube outside 5/16", plug hex head, flareless tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21913-5](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21913V5P |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-01-542-7635 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



P/N MS21913V5P Specifications

| | |
|--|--|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Head Height: | 0.172 Inches Nominal |
| Overall Length: | 0.672 Inches Nominal |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit |
| iii End Item Identification: | Mrap Buffalo Mk2a2 |
| Connection Style: | Flareless |
| Maximum Operating Pressure: | 1500.0 Pounds Per Square Inch |
| Nominal Thread Size: | 0.500 Inches External |
| Seat Angle: | 12.0 Degrees |
| Part Name Assigned By Controlling Agency: | Plug, Flareless Tube |
| Special Features: | Corrosion Resistant Steel (15-5ph) With Cadmium Plating |
| Material: | Steel Comp 15-5ph Overall |
| Media For Which Designed: | Hydraulic Fluid |
| Surface Treatment: | Cadmium Overall |
| Style Designator: | Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic |
| Thread Series Designator: | Unjf External |
| Specification/standard Data: | 81343-as21913 Professional/Industrial Association Standard |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913V5P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.