

**Description**

carbon steel, tube outside 5/16", plug hex head, flareless tube

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS21913-5](#)

SKU / Model:	MS21913V5P
Minimum Qty (MOQ):	2
NSN:	4730-01-542-7635
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N MS21913V5P Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.172 Inches Nominal
<b>Overall Length:</b>	0.672 Inches Nominal
<b>Maximum Operating Temp:</b>	275.0 Deg Fahrenheit
<b>iii End Item Identification:</b>	Mrap Buffalo Mk2a2
<b>Connection Style:</b>	Flareless
<b>Maximum Operating Pressure:</b>	1500.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.500 Inches External
<b>Seat Angle:</b>	12.0 Degrees
<b>Part Name Assigned By Controlling Agency:</b>	Plug, Flareless Tube
<b>Special Features:</b>	Corrosion Resistant Steel (15-5ph) With Cadmium Plating
<b>Material:</b>	Steel Comp 15-5ph Overall
<b>Media For Which Designed:</b>	Hydraulic Fluid
<b>Surface Treatment:</b>	Cadmium Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
<b>Thread Series Designator:</b>	Unjf External
<b>Specification/standard Data:</b>	81343-as21913 Professional/Industrial Association Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913V5P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.