

Description

Tube outside diameter: 5/8", aluminum alloy, hex head, flareless tube, MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21913W10
Minimum Qty (MOQ):	2
NSN:	4730-01-410-9978
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



* See page 2 for technical characteristics

P/N MS21913W10 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.359 Inches Nominal
Overall Length:	0.984 Inches Nominal
Maximum Operating Temp:	275.0 Deg Fahrenheit
iii End Item Identification:	Mrap Buffalo Mk2a2
Connection Style:	Flareless
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.875 Inches External
Seat Angle:	12.0 Degrees
Material:	Aluminum Alloy Body
Media For Which Designed:	Fuel/oil, Hydrocarbon And Hydraulic Fluid
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913w10 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.