

Description

tube outside: 3/16", hex head, flareless, aluminum alloy (7075), MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS21913D3](#)

SKU / Model:	MS21913W3
Minimum Qty (MOQ):	2
NSN:	4730-00-595-3917
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS21913W3 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.130 Inches Minimum And 0.150 Inches Maximum
Overall Length:	0.594 Inches Minimum And 0.624 Inches Maximum
End Item Identification:	Aircraft Fluid Systems
lii End Item Identification:	Aircraft Fluid Systems; Mrap Buffalo Mk2a2
Connection Style:	Flareless
Nominal Thread Size:	0.375 Inches External
Seat Angle:	12.0 Degrees
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out[here](#) to complete your order.