

Description

tube outside: 1/4", plug hex head, flareless, aluminum alloy, MS21913 series plug

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21913D4](#)

SKU / Model:	MS21913W4
Minimum Qty (MOQ):	5
NSN:	4730-01-140-0769
Schedule B:	7619.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



P/N MS21913W4 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.210 Inches Nominal
Overall Length:	0.641 Inches Nominal
Maximum Operating Temp:	275.0 Deg Fahrenheit
iii End Item Identification:	Mrap Buffalo Mk2a2
Connection Style:	Flareless
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.438 Inches External
Seat Angle:	12.0 Degrees
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9,t73 Fed Spec Single Material Response Overall
Media For Which Designed:	Fuel/oil, Hydrocarbon And Hydraulic Fluid
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.