

**Description**

tube outside: 1/4", plug hex head, flareless, aluminum alloy, MS21913 series plug

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS21913D4](#)

SKU / Model:	MS21913W4
Minimum Qty (MOQ):	5
NSN:	4730-01-140-0769
Schedule B:	7619.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



\* See page 2 for technical characteristics

## P/N MS21913W4 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.210 Inches Nominal
<b>Overall Length:</b>	0.641 Inches Nominal
<b>Maximum Operating Temp:</b>	275.0 Deg Fahrenheit
<b>iii End Item Identification:</b>	Mrap Buffalo Mk2a2
<b>Connection Style:</b>	Flareless
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.438 Inches External
<b>Seat Angle:</b>	12.0 Degrees
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-225/9,t73 Fed Spec Single Material Response Overall
<b>Media For Which Designed:</b>	Fuel/oil, Hydrocarbon And Hydraulic Fluid
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
<b>Thread Series Designator:</b>	Unjf External
<b>Specification/standard Data:</b>	96906-ms21913 Government Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.