

Description

aluminum alloy, tube outside 3/8", plug hex head, flareless tube, MS21913 series plug

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21913D6](#)

SKU / Model:	MS21913W6
Minimum Qty (MOQ):	5
NSN:	4730-01-027-5818
Schedule B:	7619.00.0000
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



* See page 2 for technical characteristics

P/N MS21913W6 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.200 Inches Minimum And 0.230 Inches Maximum
Overall Length:	0.704 Inches Minimum And 0.734 Inches Maximum
End Item Identification:	Mrap Buffalo Mk2a2
Connection Style:	Flareless
Nominal Thread Size:	0.562 Inches External
Seat Angle:	12.0 Degrees
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9,t73 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.