

Description

Tube outside diameter: 1/2", aluminum alloy, hex head, flareless tube, MS21913 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21913D8](#)

SKU / Model:	MS21913W8
Minimum Qty (MOQ):	2
NSN:	4730-00-202-8860
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N MS21913W8 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.281 Inches Nominal
Overall Length:	0.844 Inches Nominal
End Item Identification:	Helicopter,utility-tactical Transport,uH-1 And Eh-1 (bell)
iii End Item Identification:	Helicopter,utility-tactical Transport,uH-1 And Eh-1 (bell); Mrap Buffalo Mk2a2
Connection Style:	Flareless
Nominal Thread Size:	0.750 Inches External
Seat Angle:	12.0 Degrees
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.