

# P/N MS21913W8

## **Description**

Tube outside diameter: 1/2", aluminum alloy, hex head, flareless tube, MS21913 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### MS21913D8

SKU / Model: MS21913W8

Minimum Qty (MOQ): 2

NSN: 4730-00-202-8860

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21913W8 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.281 Inches Nominal
Overall Length:	0.844 Inches Nominal
End Item Identification:	Helicopter, utility-tactical Transport, uh-1 And Eh-1 (bell)
lii End Item Identification:	Helicopter,utility-tactical Transport,uh-1 And Eh-1 (bell); Mrap Buffalo Mk2a2
Connection Style:	Flareless
Nominal Thread Size:	0.750 Inches External
Seat Angle:	12.0 Degrees
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flareless (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms21913 Government Standard

## **How to Order**

Order this threaded tube fitting plug from our inventory online by visiting <a href="https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W8">https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/MS21913W8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.