

**Description**

tube outside diameter 3/4", corrosion resistant steel (15-5ph), cadmium plated, pressure seal, flareless, MS21914 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS21914-12](#)

SKU / Model:	MS21914V12P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-7684
Schedule B:	3926.90.9995
ECCN:	EAR99
National Motor Freight:	040500, Cap / Plug (protector)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21914V12P Specifications

<b>Thread Class:</b>	3b Internal
<b>Thread Direction:</b>	Right-hand Internal
<b>Tube Outside Diameter For Which Designed:</b>	0.750 Inches Nominal
<b>Maximum Operating Temp:</b>	225.0 Deg Fahrenheit
<b>lil End Item Identification:</b>	Mrap Buffalo Mk2a2
<b>Connection Style:</b>	Pressure Seal Flareless
<b>Thread Quantity Per Inch:</b>	12 Internal
<b>Maximum Operating Pressure:</b>	1500.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	1.062 Inches Internal
<b>Seat Angle:</b>	12.0 Degrees
<b>Part Name Assigned By Controlling Agency:</b>	Cap, Pressure Seal, Flareless Tube Fitting
<b>Special Features:</b>	Cap Assembly - Plug, Nut, Wire Retainer; Corrosion Resistant Steel With Cadmium Plating
<b>Material:</b>	Steel Comp 15-5ph Overall
<b>Media For Which Designed:</b>	Hydraulic Fluid
<b>Surface Treatment:</b>	Cadmium Overall
<b>Style Designator:</b>	Cap, Tube, Flareless
<b>Thread Series Designator:</b>	Unj Internal
<b>Specification/standard Data:</b>	81343-as21914 Professional/Industrial Association Standard

## How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/MS21914V12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.