

Description

corrosion resistant steel (15-5ph), cadmium plated, tube outside 3/16", cap, pressure seal flareless tube

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21914V3P
Minimum Qty (MOQ):	1
NSN:	4730-01-547-5929
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings

NO IMAGE
AVAILABLE

P/N MS21914V3P Specifications

Thread Class:	3b Internal
Thread Direction:	Right-hand Internal
Tube Outside Diameter For Which Designed:	0.188 Inches Nominal
Maximum Operating Temp:	275.0 Deg Fahrenheit
Connection Style:	Pressure Seal Flareless
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.375 Inches Internal
Seat Angle:	12.0 Degrees
Material:	Steel Comp 15-5ph Overall
Media For Which Designed:	Hydraulic Fluid
Surface Treatment:	Cadmium Overall
Style Designator:	Cap, Tube, Flareless
Thread Series Designator:	Unjf Internal

How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/MS21914V3P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.