

Description

corrosion resistant steel (15-5ph), cadmium plated, tube outside 1/2", pressure seal flareless tube, MS21914 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21914-8](#)

SKU / Model:	MS21914V8P
Minimum Qty (MOQ):	1
NSN:	4730-01-542-7727
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings

NO IMAGE
AVAILABLE

P/N MS21914V8P Specifications

Thread Class:	3b Internal
Thread Direction:	Right-hand Internal
Tube Outside Diameter For Which Designed:	0.500 Inches Nominal
Maximum Operating Temp:	225.0 Deg Fahrenheit
Connection Style:	Pressure Seal Flareless
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.750 Inches Internal
Seat Angle:	12.0 Degrees
Criticality Code Justification:	Feat
Part Name Assigned By Controlling Agency:	Cap, Pressure Seal, Flareless Tube Fitting
Special Features:	Cap Assembly - Plug, Nut, Wire Retainer; Corrosion Resistant Steel With Cadmium Plating
Material:	Steel Comp 15-5ph Overall
Media For Which Designed:	Hydraulic Fluid
Surface Treatment:	Cadmium Overall
Style Designator:	Cap, Tube, Flareless
Thread Series Designator:	Unjf Internal
Specification/standard Data:	81343-as21914 Professional/Industrial Association Standard

How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/MS21914V8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.