

**Description**

anodize aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21915W64
Minimum Qty (MOQ):	1
NSN:	4730-00-640-7192
ECCN:	9A991
National Motor Freight:	051400, Pipe Fittings Aluminum



\* See page 2 for technical characteristics

## P/N MS21915W6-4 Specifications

<b>Thread Class:</b>	3a 2nd End
<b>Thread Class:</b>	3b 1st End
<b>Reducer Type:</b>	Concentric
<b>Maximum Operating Temp:</b>	250.0 Deg Fahrenheit Single Response
<b>Connection Style:</b>	External Seat For Gasket Seal (boss) 2nd End
<b>Connection Style:</b>	Gasket Seal (boss) 1st End
<b>Connection Type:</b>	Threaded External Boss 2nd End
<b>Connection Type:</b>	Threaded Internal Boss 1st End
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.438 Inches 2nd End
<b>Nominal Thread Size:</b>	0.562 Inches 1st End
<b>Nominal Overall Length:</b>	1.313 Inches
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-225/6,t6,t62,t851 Fed Spec Single Material Response Overall
<b>Media For Which Designed:</b>	Hydraulic Fluid Single Response
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf All Ends
<b>Specification/standard Data:</b>	81343-as18280 Government Standard

## How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/MS21915W6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.