

## P/N MS21916D12-10

### **Description**

MS21916D12-10 Boss Reducer

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS21916D1210
Minimum Qty (MOQ):	1
NSN:	4730-00-279-0163
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21916D12-10 Specifications

Thread Class:	3a All Ends
Reducer Type:	Concentric
Connection Style:	External Seat For Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Thread Quantity Per Inch:	12 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.875 Inches 2nd End
Nominal Thread Size:	1.062 Inches 1st End
Nominal Overall Length:	1.688 Inches
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/6,t62 Jor T851 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unj 1st End
Thread Series Designator:	Unjf 2nd End
Specification/standard Data:	96906-ms21916 Government Standard

### **How to Order**

Order this boss reducer from our inventory online by visiting <a href="https://military-fasteners.com/fittings/boss+reducers/MS21916D12-10">https://military-fasteners.com/fittings/boss+reducers/MS21916D12-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/boss+reducers/MS21916D12-10">https://military-fasteners.com/fittings/boss+reducers/MS21916D12-10</a> and selecting the quantity you