

**Description**

Diameter: 13/64", rubber butadiene-acrylonitrile cushion

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21919DG24
Minimum Qty (MOQ):	10
NSN:	5340-00-286-9416
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE  
AVAILABLE

## P/N MS21919DG24 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Fuel Resistant
<b>Overall Width:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.062 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	1.234 Inches Minimum And 1.264 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.467 Inches Nominal
<b>Loop Inside Diameter:</b>	1.485 Inches Minimum And 1.515 Inches Maximum
<b>Special Features:</b>	Wedge Type Cushion Construction
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr Cushion
<b>Material Document And Classification:</b>	Ams 3215 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Qq-a-250/5 Fed Spec Single Material Response Band
<b>Surface Treatment:</b>	Chromate Band
<b>Surface Treatment Document And Classification:</b>	-1l-c-5541 Mil Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount
<b>Departure From Cited Designator:</b>	As Modified By Special Features

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919DG24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.