

P/N MS21919DG32

Description

Superseded by part number MS21919WDG32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS21919DG32
Minimum Qty (MOQ):	10
NSN:	5340-00-664-7301
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	061200, Cable Clamps / Joints Noi



^{*} See page 2 for technical characteristics

P/N MS21919DG32 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Any Acceptable
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.058 Inches Minimum And 0.068 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	1.499 Inches Nominal
Distance From Loop Center To Tongue End:	1.717 Inches Nominal
Loop Inside Diameter:	2.000 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Synthetic Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Style Designator:	Offset Mount
Nondefinitive Spec/std Data:	4 Type And A Class

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/MS21919DG32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919DG32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/MS21919DG32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/ms21919DG32 and selecting the quantity you want https://military-fasteners.com/clamps/ms21919DG32 and selecting the your cart you can check out https://military-fasteners.com/clamps/ms21919DG32 and selecting the your cart you can check out https://military-fasteners.com/clamps/ms21919DG32 and selecting the your cart your cart you can check you can ch