

Description

Diameter: 13/64", steel comp 1008 band or steel comp 1009 band or steel comp 1015 band or steel comp 1018 band or steel comp 1020 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919G56
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-200-6662
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N MS21919G56 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Weather Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	2.211 Inches Minimum And 2.241 Inches Maximum
Distance From Loop Center To Tongue End:	2.444 Inches Nominal
Loop Inside Diameter:	3.485 Inches Minimum And 3.515 Inches Maximum
Material:	Rubber Chloroprene Class Cr Cushion
Material:	Steel Comp 1008 Band Or Steel Comp 1009 Band Or Steel Comp 1015 Band Or Steel Comp 1018 Band Or Steel Comp 1020 Band
Material Document And Classification:	Ams 3209 Assn Std Single Material Response Cushion
Surface Treatment:	Cadmium Band
Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 2 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount
Nondefinitive Spec/std Data:	4 Type And B Class

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919G56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.