

## P/N MS21919H54

### **Description**

Diameter: 13/64", steel comp 1017 band

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS21919H54
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-944-5947
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21919H54 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Heat
Overall Width:	0.500 Inches Nominal
Diameter:	0.204 Inches Nominal
Material Thickness:	0.040 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	2.163 Inches Nominal
Distance From Loop Center To Tongue End:	2.381 Inches Nominal
Loop Inside Diameter:	3.375 Inches Nominal
Material:	Rubber Synthetic Cushion
Material:	Steel Comp 1017 Band
Material Document And Classification:	Qq-s-636,cond 4 Fed Spec Single Material Response Band
Surface Treatment:	Cadmium Band
Style Designator:	Offset Mount

## **How to Order**

Order this clamps from our inventory online by visiting <a href="https://military-fasteners.com/clamps/loop+clamps/MS21919H54">https://military-fasteners.com/clamps/loop+clamps/MS21919H54</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/MS21919H54">https://military-fasteners.com/clamps/loop+clamps/MS21919H54</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/MS21919H54">https://military-fasteners.com/clamps/loop+clamps/MS21919H54</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/clamps/loop+clamps/ms21919H54">https://military-fasteners.com/clamps/loop+clamps/ms21919H54</a> and selecting the quantity you want then