

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21919WCE48
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-291-0824
Schedule B:	7318.15.2091
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS21919WCE48 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Flame Resistant
Overall Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.036 Inches Minimum And 0.044 Inches Maximum
Center To Center Distance Between Loop And Mounting Hole:	1.961 Inches Minimum And 1.991 Inches Maximum
Distance From Loop Center To Tongue End:	2.179 Inches Minimum And 2.209 Inches Maximum
Loop Inside Diameter:	2.985 Inches Minimum And 3.015 Inches Maximum
Application/function:	M196.0 To P260.0 Deg C Temp Appl
Material:	Plastic Tetrafluoroethylene Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	L-p-403,type 1,class 1 Fed Spec Single Material Response Cushion
Material Document And Classification:	Mil-s-6721,comp Ti Or Cb,s32109 Mil Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount
Supplementary Features:	White Cushion W/ Red Stripe
Specification/standard Data:	96906-ms21122 Government Standard

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCE48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.