

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21919WCF18
Minimum Qty (MOQ):	10 EA
NSN:	5340-01-166-8697
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N MS21919WCF18 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.015 Inches Minimum And 1.045 Inches Maximum
Distance From Loop Center To Tongue End:	1.248 Inches Nominal
Loop Inside Diameter:	1.110 Inches Minimum And 1.140 Inches Maximum
Special Features:	Cushion Ozone Resistant
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	Ams 3215 Assn Std Single Material Response Cushion
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCF18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.