

Description

Diameter: 13/64", steel comp 321 band, MS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS21919WCF22 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-236-4457 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS21919WCF22 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Fuel Resistant |
| Overall Width: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Diameter: | 0.199 Inches Minimum And 0.209 Inches Maximum |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.140 Inches Minimum And 1.170 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.343 Inches Minimum And 1.403 Inches Maximum |
| Loop Inside Diameter: | 1.360 Inches Minimum And 1.390 Inches Maximum |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 3215 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Mil-s-6721 Mil Spec Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCF22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.