

## Description

Diameter: 13/64", steel comp 321 band, MS21919 series clamp

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS21919WCF22
Minimum Qty (MOQ):	10
NSN:	5340-01-236-4457
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS21919WCF22 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Fuel Resistant
<b>Overall Width:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Diameter:</b>	0.199 Inches Minimum And 0.209 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	1.140 Inches Minimum And 1.170 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.343 Inches Minimum And 1.403 Inches Maximum
<b>Loop Inside Diameter:</b>	1.360 Inches Minimum And 1.390 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr Cushion
<b>Material:</b>	Steel Comp 321 Band
<b>Material Document And Classification:</b>	Ams 3215 Assn Std Single Material Response Cushion
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec Single Material Response Band
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21919WCF22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.